



BS-#40-10K-120 PRODUCT NO.

V	Product number	Customer Number	Tool System	Foolproof	Max Speed
	551A100	--	BT40	NO	10,000
	551A120	--	CAT40	YES	10,000
	551A140	--	DIN40	YES	10,000
	551A160	--	MAZAK BT40	NO	10,000

Max Speed	10000 rpm
Tool System	#40
Clamping Force	700±100kgf
Spindle Bearing I.D.	4- $\phi 60$
Bearing Lubrication	Grease
Cooling System	Oil
Spindle Type	Std.
繪圖	郭俊村 2015.06.18
設計	王英權 2015.06.18
審核	黃祥峰 2015.06.18
核准	Su 2015.06.18
名稱	BS-#40-10K
圖號	551A_10K_STD Series

Spindle inclination bore runout	0.002mm
RUNOUT OF INTERNAL TAPER CONE	0.003mm(AT 15mm APART) 0.008mm(AT 300mm APART)
BALANCE GRADE	G1(ISO1940)
WEIGHT	
孔與孔中心距公差 ±0.15	加工一般公差 >0 ±0.05
鑽孔、沉頭孔公差 +0.25 -0.05 角度±0.5°	>6 ±0.10 >30 ±0.15 >120 ±0.20 >400 ±0.30 >1000±0.50
表面粗糙度	
▽:▽	▽▽:▽
▽▽:▽	▽▽▽:▽
比例	1:2.5 材質

版次	座標	更改內容	修改者	日期