

Boring - Belt Driven Block Housing (Prometrix)													
Spindle Type (Bearing Sizes mm)	Product Type	Housing Style	Type	Max Speed (rpm)	Tool System	Bearing Lubrication	Housing Width (mm)	Housing Height (mm)	Centerline Height (mm)	Max Torque (Nm)	** MTDR Torque (Nm)	Max Power/Rev (kW/rev)	Special Notes
B040-030B	Boring - Belt Driven	Block	Boring	19.5k	25.000 Pilot	Grease	115.000	125.00	65.000	106	7.5	0.0008	AirShield
B050-040B				16.5k	25.000 Pilot		130.000	135.00	70.000	146	20	0.0021	
B060-050B				13.5k	50.000 Pilot		145.000	150.00	80.000	345	55	0.0060	
B070-060B				12k	50.000 Pilot		165.000	170.00	90.000	675	110	0.0115	
B080-070B				10.5k	50.000 Pilot		180.000	185.00	100.000	1167	190	0.0204	
B090-080B				9k	50.000 Pilot		205.000	210.00	110.000	1853	295	0.0309	
B100-085B				8.25k	75.000 Pilot		215.000	225.00	120.000	1853	400	0.0419	
B120-100B				6.5k	75.000 Pilot		260.000	275.00	150.000	3318	720	0.0754	
B150-120B				5.3k	100.000 Pilot		305.000	305.00	160.000	5404	1800	0.1885	
B200-150B				3.9k	100.000 Pilot		390.000	395.00	210.000	10556	3600	0.3769	