

Boring - Belt Driven Flanged Cartridge Housing (Prometrix)											
Spindle Type (Bearing Sizes mm)	Product Type	Housing Style	Type	Max Speed (rpm)	Tool System	Bearing Lubrication	Housing Dia (mm)	Max Torque (Nm)	** MTDR Torque (Nm)	Max Power/Rev (kW/rev)	Special Notes
F040-030B	Boring - Belt Driven	Flanged Cartridge	Boring	19.5k	25.000 Pilot	Grease	110.000	106	7.5	0.0008	AirShield
F050-040B				16.5k	25.000 Pilot		120.000	146	20	0.0021	
F060-050B				13.5k	50.000 Pilot		135.000	345	55	0.0060	
F070-060B				12k	50.000 Pilot		150.000	675	110	0.0115	
F080-070B				10.5k	50.000 Pilot		165.000	1167	190	0.0204	
F090-080B				9k	50.000 Pilot		195.000	1853	295	0.0309	
F100-085B				8.25k	75.000 Pilot		205.000	1853	400	0.0419	
F120-100B				6.5k	75.000 Pilot		235.000	3318	720	0.0754	
F150-120B				5.3k	100.000 Pilot		280.000	5404	1800	0.1885	
F200-150B				3.9k	100.000 Pilot		365.000	10556	3600	0.3769	