



Setco is a leader in the design, manufacture & service of high performance precision spindles and slides. SETCO products are recognized worldwide for accuracy, durability and quality.

Visit www.setco.com to learn more about Setco and the products we offer.

View Product		C67
L x W x H (mm)	650 x 400 x 1200	
Weight (kg)	800	
Spindle Taper	HSK A63	
Max. Speed (rpm)	18,000	
Bearing Lubrication	Oil-Air	
Power (kW)	29.5kW S1 Cont. (37kW S6 40%)	
Torque	70.4Nm S1 Cont. (88.3Nm S6 40%)	
Encoder	ERM2480-600	
External Coolant	4 nozzles standard	
Cooling	Water with additives	
CTS	Option	
C Axis		
Max. Torque	1,000	
Braking Torque (Nm)	1250 (65 bar)	
Swiveling Speed (rpm)	30-40	
Rotary Angle	±115°	
Encoder system	Absolute	
Precision of Positioning	10"	
Precision of Repeatability	±3"	
A Axis		

Max. Torque	1,000
Braking Torque (Nm)	1250 (65 bar)
Swiveling Speed (rpm)	30-40
Rotary Angle	±115°
Encoder system	Absolute
Precision of Positioning	10"
Precision of Repeatability	±3"