

Grinding - Belt-Driven - Block Housing (4300G)															
Spindle Type	Product Type	Housing Style	Type	Max Speed (rpm) Rubbing Seals	Max Speed (rpm) Labyrinth Seals	Male Taper Gage Dia (in)	Taper (in/ft)	Bearings (mm)	Bearing Lubrication	Housing Width (in)	Housing Height (in)	Centerline Height (in)	Max Torque Rating (in*lbs)	Max Torque (Hp/Rev)	Weight (lbs)
4301G	Grinding - Belt-Driven	Block	Grinding	4400	15000	1.001/.999	3.000	30	Grease	4.00	3.62	2.000	50	0.0008	45
4302G				3700	13000			35		4.50	4.12	2.250	60	0.0010	50
4303G				3000	10800	1.626/1.624		45		4.94	4.50	2.500	70	0.0011	65
4304G				2200	8300			2.251/2.249		60	5.50	5.50	3.188	500	0.0080
4305G				2100	7400	65				6.50	6.25	3.500	900	0.0140	155
4307G				1900	6800	2.626/2.624		70		7.00	7.00	4.000	950	0.0166	210
4308G				1700	6000	3.001/2.999		80		8.50	8.00	4.500	1700	0.0250	295
4309G				1400	4800	3.751/3.749		100		10.00	9.50	5.500	3550	0.0500	500
4310G				1200	4500	4.501/4.499		120		10.00	10.00	5.500	6350	0.1000	745
4311G				1000	3800	5.001/4.999		140		11.00	11.50	6.000	7950	0.1250	1025