

Grinding - Belt-Driven - Flanged Cartridge Housing (4100G)

Spindle Type	Product Type	Housing Style	Type	Max Speed (rpm) Rubbing Seals	Max Speed (rpm) Labyrinth Seals	Male Taper Gage Dia (in)	Taper (in/ft)	Bearings (mm)	Bearing Lubrication	Housing Cartridge Dia (in)	Housing Flange Dia (in)	Max Torque Rating (in*lbs)	Max Torque (Hp/Rev)	Weight (lbs)
4101G	Grinding - Belt-Driven	Flanged Cartridge	Grinding	4400	15000	1.001/.999	3.000	30	Grease	2.9990	4.25	50	0.0008	45
4102G				3700	13000			35		3.4990	4.75	60	0.0010	50
4101G				3000	10800	45		3.9990		5.25	70	0.0011	65	
4104G				2200	8300	60		4.6240		6.62	500	0.0080	110	
4105G				2100	7400	65		5.4990		7.25	900	0.0140	155	
4107G				1900	6800	70		5.9990		7.75	950	0.0166	210	
4108G				1700	6000	80		6.9990		9.00	1700	0.0250	295	
4109G				1400	4800	100		7.9990		10.00	3550	0.0500	500	
4110G				1200	4500	120		8.9990		11.50	6350	0.1000	745	
4111G				1000	3800	140		9.9990		12.50	7950	0.1250	1025	