

Grinding - Belt-Driven - Foot Mount Housing (4200G)														
Spindle Type	Product Type	Housing Style	Type	Max Speed (rpm) Rubbing Seals	Max Speed (rpm) Labyrinth Seals	Male Taper Gage Dia (in)	Taper (in/ft)	Bearings (mm)	Bearing Lubrication	Housing Foot Width (in)	Centerline Height (in)	Max Torque Rating (in*lbs)	Max Torque (Hp/Rev)	Weight (lbs)
4201G	Grinding - Belt-Driven	Foot Mount	Grinding	4400	15000	1.001/.999	3.000	30	Grease	6.50	2.000	50	0.0008	45
4202G				3700	13000			35		7.00	2.250	60	0.0010	50
4202G				3000	10800	45		8.00		2.500	70	0.0011	65	
4204G				2200	8300	60		8.50		3.188	500	0.0080	110	
4205G				2100	7400			2.251/2.249		8.50	3.500	900	0.0140	155
4207G				1900	6800	70		9.00		4.000	950	0.0166	210	
4208G				1700	6000	80		12.00		4.500	1700	0.0250	295	
4209G				1400	4800	100		14.00		5.500	3550	0.0500	500	
4210G				1200	4500	120		14.00		5.500	6350	0.1000	745	
4211G				1000	3800	140		14.00		6.000	7950	0.1250	1025	