

Grinding - Belt-Driven - I-Beam Shaped Housing (4300G)																
Spindle Type	Product Type	Housing Style	Type	Max Speed (rpm) Rubbing Seals	Max Speed (rpm) Labyrinth Seals	Male Taper Gage Dia (in)	Taper (in/ft)	Bearings (mm)	Bearing Lubrication	Housing Foot Width Btm (in)	Housing Foot Width Top (in)	Housing Height (in)	Centerline Height (in)	Max Torque Rating	Max Torque (Hp/Rev)	Weight (lbs)
4401G	Grinding - Belt-Driven	I-Beam Shaped	Grinding	4400	15000	1.001/.999	3.000	30	Grease	6.50	9.50	3.62	2.000	50	0.0008	45
4402G				3700	13000			35		7.00	9.50	4.12	2.250	60	0.0010	50
4404G				3000	10800			45		8.00	10.00	4.50	2.500	70	0.0011	65
4404G				2200	8300	2.251/2.249		60		8.50	11.00	5.50	3.188	500	0.0080	110
4405G				2100	7400			65		8.50	11.00	6.25	3.500	900	0.0140	155
4407G				1900	6800	2.626/2.624		70		9.00	12.00	7.00	4.000	950	0.0166	210
4408G				1700	6000	3.001/2.999		80		12.00	14.00	8.00	4.500	1700	0.0250	295
4409G				1400	4800	3.751/3.749		100		14.00	16.00	9.50	5.500	3550	0.0500	500
4410G				1200	4500	4.501/4.499		120		14.00	18.00	10.00	5.500	6350	0.1000	745
4411G				1000	3800	5.001/4.999		140		14.00	18.00	11.50	6.000	7950	0.1250	1025