

Grinding - Motorized - Foot Mount (6100G)												
Spindle Type	Product Type	Size	Power (Hp)	Speed (rpm)	Male Taper Gage Dia (in)	Taper (in/ft)	Bearings (mm)	Bearing Lubrication	Housing Foot Width (in)	Housing Height (in)	Centerline Height (in)	Weight (lbs)
6100.5.36G	Grinding - Motorized	5	0.50	3600	1.001/.999	3.000	35/20	Grease	7.50	6.62	3.001/2.999	75
6100.5.18G			0.50	1800								70
6100.5.12G			0.50	1200								70
6100.7.36G			0.75	3600								75
6100.7.18G			0.75	1800								70
6101.36G			1.00	3600								75
6101.18G			1.00	1800								75
6101.5.36G			1.50	3600								75
6100.7.12G		6	0.75	1200	1.251/1.249	3.000	40/25	Grease	8.00	6.94	3.501/3.499	80
6101.12G			1.00	1200								85
6101.5.18G			1.50	1800								85
6101.5.12G			1.50	1200								85
6102.36G			2.00	3600								85
6102.18G			2.00	1800								90
6103.36G		3.00	3600	90								
6101.5.09G		8	1.50	900	1.251/1.249	3.000	50/30	Grease	9.75	8.38	4.251/4.249	122
6102.12G			2.00	1200								127
6103.18G			3.00	1800								127
6105.36G			5.00	3600								130
6102.09G		10	2.00	900	1.626/1.624	3.000	60/45	Grease	12.00	10.00	5.001/4.999	260
6103.12G			3.00	1200								250
6105.18G			5.00	1800								260
6105.12G			5.00	1200								290
6107.5.36G			7.50	3600								275
6107.5.18G			7.50	1800								300
6110.36G		10.00	3600	320								
6103.09G		12	3.00	900	3.001/2.999	3.000	80/45	Grease	15.00	15.50	6.251/6.249	440
6105.09G			5.00	900								450
6107.5.12G			7.50	1200								445
6107.5.09G			7.50	900								460
6110.18G			10.00	1800								490
6110.12G			10.00	1200								490
6115.36G	15.00		3600	490								
6115.18G	15.00		1800	500								
6120.36G	20.00		3600	500								
6120.18G	20.00		1800	520								