

Grinding - Motorized - Surface & Internal Grinding Bracket Mount (2700G)

Spindle Type	Product Type	Size	Power (Hp)	Speed (rpm)	Male Taper Gage Dia (in)	Taper (in/ft)	Bearings (mm)	Bearing Lubrication	Housing Foot Width (in)	Housing Height (in)	Centerline Height (in)	Weight (lbs)
2700.5.36G	Grinding - Motorized	5	0.50	3600	1.001/.999	3.000	30/40	Grease	7.50	5.75	3.001/2.999	65
2700.5.18G			0.50	1800								70
2700.5.12G			0.50	1200								72
2700.7.36G			0.75	3600								74
2700.7.18G			0.75	1800								72
2701.36G			1.00	3600								74
2701.18G			1.00	1800								74
2701.5.36G			1.50	3600								74
2700.7.12G		6	0.75	1200	1.001/.999	3.000	30/40	Grease	8.50	6.75	3.501/3.499	77
2701.12G			1.00	1200								79
2701.5.18G			1.50	1800								79
2701.5.12G			1.50	1200								83
2702.36G			2.00	3600								83
2702.18G			2.00	1800								85
2703.36G			3.00	3600								85
2701.5.09G		8	1.50	900	1.626/1.624	3.000	45/60	Grease	9.75	8.13	4.126/4.124	145
2702.12G			2.00	1200								150
2703.18G			3.00	1800								180
2705.36G			5.00	3600								200
2702.09G		10	2.00	900	2.251/2.249	3.000	60/70	Grease	11.75	10.13	5.126/5.124	310
2703.12G			3.00	1200								310
2705.18G			5.00	1800								320
2705.12G			5.00	1200								340
2707.5.36G			7.50	3600								340
2707.5.18G	7.50		1800	370								
2710.36G	10.00		3600	370								