

Grinding - Motorized - Surface & Internal Grinding Foot Mount (2800G)

Spindle Type	Product Type	Size	Power (Hp)	Speed (rpm)	Male Taper Gage Dia (in)	Taper (in/ft)	Bearings (mm)	Bearing Lubrication	Housing Foot Width (in)	Housing Height (in)	Centerline Height (in)	Weight (lbs)
2700.5.36G	Grinding - Motorized	5	0.50	3600	1.001/.999	3.000	30/40	Grease	7.50	5.75	3.001/2.999	75
2700.5.18G			0.50	1800								80
2700.5.12G			0.50	1200								82
2700.7.36G			0.75	3600								84
2700.7.18G			0.75	1800								82
2701.36G			1.00	3600								84
2701.18G			1.00	1800								84
2701.5.36G			1.50	3600								84
2700.7.12G		6	0.75	1200	1.001/.999	3.000	30/40	Grease	8.50	6.75	3.501/3.499	87
2701.12G			1.00	1200								89
2701.5.18G			1.50	1800								89
2701.5.12G			1.50	1200								93
2702.36G			2.00	3600								93
2702.18G			2.00	1800								95
2703.36G		3.00	3600	95								
2701.5.09G		8	1.50	900	1.626/1.624	3.000	45/60	Grease	9.75	8.13	4.126/4.124	185
2702.12G			2.00	1200								190
2703.18G			3.00	1800								220
2705.36G			5.00	3600								240
2702.09G		10	2.00	900	2.251/2.249	3.000	60/70	Grease	11.75	10.13	5.126/5.124	360
2703.12G			3.00	1200								360
2705.18G			5.00	1800								370
2705.12G			5.00	1200								390
2707.5.36G			7.50	3600								390
2707.5.18G	7.50		1800	420								
2710.36G	10.00		3600	420								